

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
16 October 2003 (16.10.2003)

PCT

(10) International Publication Number
WO 03/085231 A1

- (51) International Patent Classification⁷: **E21B 10/56** (74) Agent: CARLSSON Lars-Åke; Sandvik AB, Intellectual Property, S-811 81 Sandviken (SE).
- (21) International Application Number: PCT/SE03/00494
- (22) International Filing Date: 26 March 2003 (26.03.2003) (81) Designated States (*national*): AT, AU, CA, CN, DE, FI, GB, IN, JP, KR, RU, SE, US, ZA.
- (25) Filing Language: English
- (26) Publication Language: English (84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (30) Priority Data:
0201034-6 4 April 2002 (04.04.2002) SE
- (71) Applicant (*for all designated States except US*): SANDVIK AB [SE/SE]; S-811 81 Sandviken (SE). Published:
— with international search report
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): BJÖRK, Fredrik [SE/SE]; Västanbygatan 18, S-811 32 Sandviken (SE). For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PERCUSSION DRILL BIT AND A BUTTON THEREFOR



(57) Abstract: A percussion drill bit for drilling a bore, comprising a drill body having a connecting section at a rear end thereof for connection to a percussive unit and defining a rotational axis (CL1) of the drill bit, and a plurality of cemented carbide buttons (7, 9, 10) embedded in a front end of the drill body. The front end being rigid with respect to the connecting section. Each button comprises a cemented carbide body having a rear mounting portion (20) embedded in the drill body, and a front end (18) protruding from the drill body. The front end of the cemented carbide button is substantially semi-spherically curved and defined by a radius (R2). An origin (C) of the radius is disposed axially rearwardly of a plane (P) defines the largest diameter (D) of the button. The button projects from the drill bit body a distance (L2), which is not less than 50 % of the button diameter (D). A conical intermediate surface (21) forms, in cross-section, an acute angle (α) of about 13-19° with the envelope surface (25) of the rear mounting portion (20). The present invention also relates to the button itself, i.e. a cemented carbide button for use in a percussive drill bit.

WO 03/085231 A1